




Material Safety Data Sheet

Product Name: Defoamer Code: 6500

WHMIS	Protective Clothing	TDG Road / Rail
		

SECTION I – PRODUCT IDENTIFICATION AND PREPERATION INFORMATION

Product Name: Defoamer **Effective Date:** Sep. 7, 06 **Code:** 6500
Product Use: Not available
WHMIS: WHMIS Class D-2B: Material causing other toxic effects (TOXIC)
TDG: Not regulated under TDG (Canada).

Supplier: **Formula Canada**
3069 Dundas Street West
Toronto, Ontario M6P 1Z5
(416) 743-6660

EMERGENCY PHONE: CANUTEC (613) 996-6666

SECTION II – HAZARDOUS INGREDIENTS

Ingredients	CAS #	Wt%	ACGIH-TLV	LC ₅₀ /LD ₅₀
Isopropyl alcohol	67-63-0	1-5	TWA: 400 CEIL: 500 (ppm) TWA: 900 CEIL: 1225 (mg/m ³)	ORAL (LD ₅₀): Acute: 3600 mg/kg (Mouse) VAPOR (LC ₅₀): Acute: 16970 ppm 4 hours (Rat).

SECTION III – PHYSICAL DATA

Boiling Point:	100°C (212°F).	Specific Gravity:	Weighted average: 1.03 (Water = 1.00)
Vapour Pressure:	The highest known value is 33 mm of Hg (@ 20°C) (Isopropyl alcohol). Weighted average: 17.02 mm of Hg (@ 20°C)	Vapour Density:	The highest known value is 5 (Air=1) (Pine oil). Weighted average: 3.29 (Air=1).
Solubility in Water:	Soluble	Percent Volatile:	Not available.
Physical State:	Liquid	Evaporation Rate:	Not available.
Appearance and Odour:	White / Silicone.	pH (as supplied):	7.5

SECTION IV – FIRE AND EXPLOSION DATA

Flammability:	Non-combustible.
Flash Points:	The lowest known value is CLOSED CUP: 11.6oC (53oF). OPEN CUP: 18.3oC (64.9oF) Cleveland. (Isopropyl alcohol)
Flammable Limits:	The greatest known range is LOWER 2% UPPER 12% (Isopropyl alcohol).
Hazardous Combustion Products:	These products are carbon oxides (CO, CO ₂). Some metallic oxides.
Means of Extinction:	SMALL FIRE: Use DRY chemicals, CO ₂ , alcohol foam or water spray. LARGE FIRE: Use alcohol foam, water spray or fog.
Special Fire Hazards:	No explosive sensitivity.

Continued...

Material Safety Data Sheet

Product Name: Defoamer Code: 6500

SECTION V – REACTIVITY DATA

Stability: The product is stable
Incompatibility: Reactive with oxidizing agents. Non-reactive with metals.
Hazardous Decomposition Products: Not known to use at this time.

SECTION VI – TOXICOLOGICAL PROPERTIES

Routes of Entry: Absorbed through skin. Ingestion.
Acute Effects on Humans: Hazardous in case of skin contact (sensitizer, permeator), of ingestion. Slightly hazardous in case of skin contact (irritant), of eye contact (irritant), of inhalation. Sever over-exposure can result in death.
Chronic Effects on Humans: CARCINOGENIC: Not available.
MUTAGENIC EFFECTS: Not available.
TERATOGENIC EFFECTS: Not available.
DEVELOPMENTAL TOXICITY: PROVEN (Isopropyl alcohol) – The substance is toxic to gastro-intestinal tract, upper respiratory tract, the reproductive system.
Repeated exposure to a highly toxic material may produce general deterioration of health by an accumulation in one or many human organs.
Synergistic Materials: Not available.

SECTION VII – PREVENTATIVE MEASURES

Gloves: Seamless neoprene gloves.
Eye Protection: Splash goggles.
Respiratory Protection: General ventilation normally adequate. Respiratory protection nor normally required.
Other Protective Equipment: Other protective equipment as required by employer code.
Engineering Controls: Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapours below their respective threshold limit value. Ensure that eyewash stations and safety showers are proximal to the workstation location.
Leak and Spill Procedure: Dilute with water and mop up, or absorb with an inert material and put the spilled material in an appropriate waste disposal. If necessary, Neutralize the residue with a dilute solution of acetic acid. Corrosive liquid. Stop leak if without risk. Absorb with DRY earth, sand or other non-combustible material. DO NOT get water inside container. DO NOT touch spilled material. Use water spray curtain to divert vapour drift. Prevent entry into sewers, basements or confined areas; dike if needed. Call for assistance on disposal. Neutralize the residue with a dilute solution of acetic acid. Be careful that the product is not present at a concentration level above TLV. Check TLV on the MSDS and with local authorities.
Waste Disposal: Consult municipal, provincial, and federal laws.
Storage Requirements: Keep container tightly closed. Keep from freezing. Keep in a cool, well-ventilated place. Keep out of reach of children.

SECTION VIII – FIRST AID

Eye: In case of contact with eyes, rinse immediately with plenty of water for 15 minutes. Finish by rinsing thoroughly with running water to avoid a possible infection. If irritation persists, seek medical attention.
Skin: Rinse skin with clean water. If irritation persists, seek medical attention.
Inhalation: Allow the victim to rest in a well ventilated area. Seek medical attention.
Ingestion: DO NOT induce vomiting. Examine the lips and mouth to ascertain whether the tissues are damaged, a possible indication that the toxic material was ingested; the absence of such signs, however, is not conclusive. Loosen tight clothing such as a collar, tie, belt, or waistband. If the victim is not breathing, perform mouth-to-mouth resuscitation. Seek immediate medical attention.

SECTION IX – PREPERATION / OTHER INFORMATION

References: Not available.
Additional Remarks: No additional remark.

Validated by Formula Canada on September 7, 2006

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Formula Canada expressly disclaims all expressed or implied warranties of merchantability and fitness for a particular purpose with respect to the product provided.